

VARIABLE FLOW DEPOSITION APPARATUS AND METHOD
IN SEMICONDUCTOR SUBSTRATE PROCESSING

5 FIELD OF THE INVENTIONS

[0001] These inventions relate to a novel vacuum processing chamber and method for processing substrates. More particularly, this invention relates to a vacuum processing chamber and processing method in
10 which deposition gasses are admitted and exhausted from the chamber.

BACKGROUND OF THE INVENTIONS

[0002] Single substrate processing chambers for substrates such as silicon wafers, have been used for some time because among other reasons,
15 the chamber volume can be minimized, contamination of the substrate can be reduced, and the process control increased such that yields can be improved. Further, vacuum systems have been developed, such as described in Maydan et al, U.S. Pat. No. 4,951,601, that allow several sequential processing steps to be carried out in a plurality of vacuum processing
20 chambers connected to a central transfer chamber, so that several processing steps can be performed on a substrate without its leaving a vacuum environment. This can further reduce contamination of the substrates.

[0003] Other types of substrates are also processed in vacuum
25 systems. For example, large glass substrates having active thin film transistors can be used as active matrix television and computer displays. Some glass substrates can be as large as a meter in length or longer. The basic methods and processing chambers, e.g., plasma enhanced chemical vapor deposition (PECVD), physical vapor deposition (PVD), etch chambers
30 and the like, can be used for glass substrates in a manner similar to those used for depositing layers and patterning thin films on silicon wafers.

[0004] In conventional single substrate PECVD chambers, the substrate to be processed is typically supported by a heated susceptor and

reaction gases are fed to the chamber via a gas dispersion plate mounted above and generally parallel to the substrate. The gas dispersion plate and susceptor can be connected across an RF source such that when power is turned on in the presence of a precursor gas, a plasma forms in the region
5 between the gas dispersion plate and the substrate. Typically, the heated susceptor is movable to elevate the substrate to a desired position below the gas dispersion plate to improve the uniformity of deposition.

[0005] One deposition method provides a continuous flow of gasses through the chamber in which a first reaction gas is added to the flow,
10 followed by a purge gas, a second reaction gas and again a purge gas. This sequence is cycled many times (typically, 25-200 cycles, depending upon the particular process) until a desired thickness is achieved. For example, one continuous flow process deposits a layer which is approximately 1 Angstrom thick each cycle and the cycle is repeated until approximately 25- 200
15 Angstroms is deposited onto the substrate. During the deposition, the exhaust outlet of the chamber is kept substantially open to permit the continuous flow of the gas mixtures through the chamber.

[0006] Materials deposited in such continuous processes include tungsten, titanium, titanium chloride, and other materials which are suitable to
20 be vaporized or evaporated and injected into a stream. In some deposition processes such as atomic layer deposition (ALD), each deposition gas is injected into the chamber in a relatively short pulse during each of the deposition cycles. For example, a deposition gas injection pulse may be on the order of a half second or less.

[0007] Another deposition method introduces a deposition gas into
25 the chamber in which the exhaust outlet is sealed so that relatively high pressures of the deposition gas may be achieved in the chamber. This deposition method is considered to be noncontinuous in that the chamber admits a quantity of reaction gas and holds it until the desired deposition
30 thickness has been achieved. The chamber exhaust outlet is then unsealed and opened and the deposition gas is purged from the chamber. The

exhaust outlet valves tend to be relatively slow to open because the seals may need to decompress or may otherwise delay the opening of the outlet valve. Materials deposited in such non-continuous depositions include aluminum, for example, which may be deposited in a chamber atmosphere of several thousand p.s.i.

- 5 [0008] By manipulation of gas flows, temperatures, and pressure in the chamber maintained by a vacuum exhaust system, most of the particulates in the plasma region can be carried by the gases away from the susceptor and substrate and to the exhaust system. U.S. pat. No. 5,582,866,
- 10 which is assigned to the assignee of the present application, discloses a vacuum exhaust system which includes a plenum chamber connected to an exhaust port and vacuum pump. The plenum chamber is built into the lid so as to completely surround the gas dispersion plate and be above and surrounding the substrate periphery. A non-sealing, pressure-controlling
- 15 throttle valve coupled to the exhaust port can control the flow of material from the chamber through the pump.

SUMMARY OF THE INVENTIONS

[0009] In one embodiment of the present inventions, an exhaust outlet in a vacuum processing chamber includes a nonsealing flow restrictor which can facilitate rapid opening and closing of the flow restrictor in some applications. Such a flow restrictor may be used in a variety of different chambers and deposition methods. It is believed that a nonsealing flow restrictor in accordance with the present invention is well suited to fast cycle deposition sequences such as atomic layer depositions (ALD).

[0010] Because the flow restrictor is a nonsealing flow restrictor, the conductance of the flow restrictor in the closed position may not be zero. However, the flow restrictor can restrict the flow of an exhaust gas from the chamber to permit the retention of sufficient processing gas in the chamber to deposit a film on the substrate or otherwise react with the substrate. In a preferred embodiment, the flow restrictor is a near sealing flow restrictor. After the desired film has been deposited or the processing of the substrate has been completed, the exhaust flow restrictor may be opened such that the flow restrictor conductance is significantly increased to a second, higher flow rate to facilitate exhausting residue gas from the chamber.

[0011] The closing and opening of the exhaust flow restrictor may be repeated as many times as needed to deposit additional layers onto the substrate until the desired thickness is achieved. In one embodiment, an atomic layer is deposited each cycle of the closing and opening of the exhaust flow restrictor. It is contemplated that different deposition materials may be alternately deposited as the deposition builds up onto the substrate.

[0012] A vacuum processing chamber in accordance with one embodiment comprises a plenum chamber coupled to an exhaust port and vacuum pump, in which plenum chamber is built into or adjacent to the lid so as to completely surround the substrate periphery. The near sealing exhaust flow restrictor when open couples the plenum chamber to the plasma processing region above the substrate. The near sealing exhaust flow restrictor, like the plenum, also surrounds the substrate. The flow restrictor

passageway or passageways may be positioned around the substrate such that spent gases and particulates may be withdrawn from the plasma processing region in a desired fashion.

[0013] There are additional aspects to the present inventions. It

- 5 should therefore be understood that the preceding is merely a brief summary of some embodiments and aspects of the present inventions. Additional embodiments and aspects of the present inventions are referenced below. It should further be understood that numerous changes to the disclosed embodiments can be made without departing from the spirit or scope of the
- 10 inventions. The preceding summary therefore is not meant to limit the scope of the inventions. Rather, the scope of the inventions is to be determined by appended claims and their equivalents.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014]

Fig. 1 is a cross sectional view of a single substrate ALD chamber in accordance with aspects of the present inventions.

5

Fig. 2 is a schematic chart illustrating a process in accordance with aspects of the present inventions using the chamber of Fig. 1.

Fig. 3 is an enlarged view of the nonsealing flow restrictor of Fig. 1.

10

Fig. 4 is a schematic view of the chamber body top of Fig. 1.

Fig. 5 is a cross sectional view of a single substrate ALD chamber in accordance with an alternative embodiment.

15

Fig. 6 is an enlarged view of the nonsealing flow restrictor of Fig. 5.

DETAILED DESCRIPTIONS OF EXEMPLARY EMBODIMENTS

20 [0015] A processing chamber in accordance with a preferred embodiment of various aspects of the present inventions is indicated generally at 100 in Fig. 1. The processing chamber 100 includes a substrate support 102 having a support surface 106 which supports a substrate 108 in position for deposition of a layer of deposition material. The substrate 108
25 may be a silicon wafer, for example, or a glass substrate or other substrates upon which a layer of material may be deposited. Although the illustrative chamber 100 is depicted as a single substrate chamber, it is appreciated that the present inventions may be used in connection with multiple substrate chambers as well.

30 [0016] Fig. 2 illustrates in schematic form a typical process ~~120 for depositing material on to a substrate such as the substrate 108 using the~~

Sub
A2
conc.

chamber 100. As explained in greater detail below, the present inventions have particular applicability to deposition processes such as atomic layer depositions in which many very thin layers are deposited in rapid succession onto the substrate. As indicated generally at 122, a typical process is initiated by admitting a substrate into the chamber through a slit valve or other suitable substrate port 124 (Fig. 1) and onto the support surface 106 for processing. A heater 128 may be provided within the substrate support 102 to heat the substrate 108, depending upon the particular deposition process.

[0017] The deposition material is preferably admitted into the chamber 100 in the form of a deposition gas through one or more suitable chamber inlets such as the gas inlet 140. The flow of deposition material from each inlet into the chamber is controlled by a suitable inlet flow control valve 141 which may include sealing and non-sealing devices. Following deposition of a layer, a certain amount of residue gasses typically remain in the chamber. These residue gasses can include undeposited gasses as well as reaction byproducts in gas or particulate form suspended within the chamber gasses. The residue gasses are usually preferably removed from the chamber prior to admitting additional deposition gas to deposit the next layer. In accordance with one aspect of the present inventions, the chamber 100 has an exhaust outlet 150 which can facilitate rapid substrate processing and inhibit particle generation. In the illustrated embodiment, the exhaust outlet 150 includes an exhaust passageway 152 and an exhaust flow restrictor 154 which, in the open position (Fig. 1), defines a flow restrictor passageway 156 which couples the chamber processing area 142 above the substrate to the exhaust outlet passageway 152 to exhaust the residue gasses from the chamber.

[0018] In a preferred embodiment, the exhaust flow restrictor 154 is a non-sealing flow restrictor such that in the closed position (Fig. 3), it is anticipated that the flow restrictor passageway 156 may not be entirely closed. It has been recognized by the present applicants that for some non-continuous deposition processes, satisfactory results may be achieved

without a complete sealing of the exhaust outlet of the chamber during the deposition. Moreover, by eliminating or reducing sealing elements such as seal rings and the like from the exhaust flow restrictor 154, it is believed that the exhaust flow restrictor 154 may be operated more quickly and the
5 generation of particles reduced.

[0019] For example, prior to admitting or during the admission of deposition gas, the exhaust flow restrictor 154 may be closed (step 170 of Fig. 2) to facilitate achieving an adequate deposition gas pressurization level in the chamber during the deposition process. As indicated at 172 in Fig. 2,
10 the closing of the exhaust flow restrictor 154 initiates a "pressure cycle" in which the pressure of the chamber is increased for deposition. Thus, following closing of the exhaust flow restrictor 154 a processing gas such as a deposition gas is admitted (or continued to be admitted) into the chamber through the gas inlet 140 as represented by step 173 in the process of Fig. 2.
15 Because the flow restrictor 154 is closed, the pressure in the chamber will rise. However, because the exhaust flow restrictor 154 in the embodiment of Fig. 1 is not a sealing type flow restrictor, it is anticipated that some deposition gas may escape through the closed flow restrictor 154 during the deposition process. However, as long as the flow rate through the closed
20 flow restrictor 154 is less than the flow rate through the inlet flow valve 141, it is believed that the pressure in the chamber can rise to the desired level notwithstanding leakage through the exhaust flow restrictor 154. In a preferred embodiment, the flow rate through the closed flow restrictor is within a range of 0 – 100 sccm (standard cubic centimeter per minute) at a pressure
25 in the range of 10 Torr to 300 Torr. Thus, the flow restrictor can be a near sealing flow restrictor which has a relatively low flow rate in the "closed" position.

[0020] Once the desired pressure level has been achieved, the flow valve of the deposition gas inlet 140 may be closed. For some deposition
30 processes, it may be desirable to permit the substrate 108 to soak in the deposition gas atmosphere (step 174, Fig. 2) in the interior of the chamber for

sub
A3
conc.

a length of time following the closing of the gas inlet to ensure an adequate deposition thickness. To ensure adequate deposition gas pressure during the soaking period, the deposition gas pressure may be raised prior to closing the gas inlet to a level which would accommodate some leakage through the exhaust flow restrictor during the soaking period. In one embodiment, the pressure may rise to a level of 300 Torr, for example. Thus, although the deposition gas pressure may fall somewhat during the soaking period because of some leakage through the nonsealing exhaust flow restrictor, the deposition gas pressure at the end of the soaking period may still be sufficiently high to ensure a satisfactory deposition. In a preferred embodiment, the deposition gas pressure for a typical deposition gas may fall to a level in a range of 5 – 30 Torr.

[0021] The duration of the pressure cycle will be dependent to a large extent upon the material selected, the desired layer thickness and the deposition pressure. For many processes, it is believed that a pressure cycle of less than 10 seconds in duration will be suitable for many deposition materials. Because the duration of each pressure cycle is typically relatively short, relatively little deposition gas will escape through the near sealing flow restrictor during each pressure cycle.

[0022] Once the substrate has soaked in the deposition gas for a sufficient length of time to deposit the desired thickness of deposition material, the pressure cycle 172 may be ended by opening the exhaust flow restrictor 154 (step 180, Fig. 2) as shown in Fig. 1 to permit the residue gasses to be readily exhausted from the chamber interior during a "purge cycle" as indicated at 182 in Fig. 2. In this open position, the exhaust flow restrictor 154 preferably has sufficient conductance to permit rapid exhaustion of the residue gasses. In a preferred embodiment, the non-sealing flow restrictor 154 has a conductance in the range of 10 –20 slm (standard liter per minute) in the open position. By comparison, the conductance of the near sealing flow restrictor 154 in the closed position illustrated in Fig. 2 is preferably much smaller and is preferably close to zero but it is anticipated

sub
A4

sub
A4
cont

that the conductance will be somewhat greater than zero because the flow restrictor is a non-sealing flow restrictor. In a preferred embodiment, the near sealing flow restrictor 154 has a conductance in the range of 0 - 100 sccm in the closed position.

5 [0023] To facilitate exhausting the residue gasses from the chamber, a pump 200 may be coupled to an outlet port 202 of the exhaust outlet 150 as shown in Fig. 4. In addition one or more purge gasses may be admitted into the chamber as indicated in step 204 (Fig. 2), to drive the residue gas from the chamber interior as the pump 200 pumps the gasses
10 through the exhaust flow restrictor 154, through the exhaust passageway 152 and out of the chamber through the outlet port 202. Once the chamber has been sufficiently purged, a different reactant or deposition gas may be admitted to deposit another thin layer.

[0024] In the process of Fig. 2, there is a plurality of pressure cycles
15 172, each followed by a purge cycle 182, to sequentially deposit a plurality of layers onto a substrate before the substrate is removed from the chamber. In each pressure cycle 172, the non-sealing flow restrictor 154 is closed and a process gas such as a deposition gas is admitted. After a layer has been deposited, the non-sealing flow restrictor is opened and residue gasses are
20 discharged in the subsequent purge cycle 182. The process gas or gasses may be the same in each pressure cycle or may change, depending upon the desired process.

[0025] In the embodiment of Fig. 2, a first reactant gas is admitted in the gas admission step 173 of the first pressure cycle 172. After the
25 subsequent purge cycle 182, a pressure cycle 206 follows which is similar to the pressure cycle 172 except that following the closing of the exhaust flow restrictor (step 208) a second, different reactant gas is admitted in an admission step 210 of this next pressure cycle 206. During the pressure cycle 206, the second reactant is deposited onto or otherwise reacts with the
30 first reactant deposited in the prior pressure cycle 172 (step 212) to form another thin layer on the substrate. Examples of deposition materials in a

Sub
A4
conc.

second pressure cycle include nitrogen, oxygen or silicon which can react with the previously deposited material to form a nitride, oxide or silicide, respectively.

[0026] Following each pressure cycle 206, a purge cycle 214 similar to the purge cycle 182, opens the non-sealing exhaust flow restrictor 154 (step 216) to purge the undeposited second reactant from the chamber using a purge gas (step 218). The pressure cycles 172 and 206 alternate in this manner, depositing alternating layers of the first and second reactants, each pressure cycle being followed by an associated purge cycle 182, 214, until the desired film thickness has been deposited (or the film processing is otherwise complete). After the final purge cycle 214, the slit valve 124 is opened and the substrate is removed from the chamber as shown in step 220 of Fig. 2. Because of the rapid opening and closing capabilities of the flow restrictor 154, it is believed that the combined total of the pressure cycle and the purge cycle may be in a range of 5 - 20 seconds and more typically 10 seconds for many applications. However, the exhaust flow restrictor is suitable for substantially shorter cycles of .5 seconds or less, depending upon the application. Other pressure cycles may be 5 seconds or 3 seconds or less, depending upon the application.

[0027] In the illustrated embodiment, the chamber 100 includes two principal parts, a lid portion 302 (see FIG. 1) and a processing chamber body portion 304. The two parts 302, 304 are attached by means of a hinge 305. A vacuum pressure is maintained in the chamber when the lid is closed by means of one or more O-ring seals 306. In this manner, a pressure vessel may be formed by the joining of the two parts.

[0028] The exhaust outlet 150 includes a plenum chamber 326 which is formed when the lid portion 302 is closed onto the chamber body portion 304. The plenum chamber 326 has a top wall 328 (Fig. 1) provided by the lid portion 302 and an outer side 330 (Fig. 4) and a bottom wall 332 provided by the chamber walls of the body portion 304. The plenum chamber 326 defines an interior 334 (Fig. 1) which is generally annular shaped (Fig. 4)

and completely surrounds the processing region 142 above the substrate support 102. The annular plenum may be circular shaped, rectangular shaped or have another shape, depending upon the shape of the chamber and the shape of the substrate being processed.

5 **[0029]** The outlet flow restrictor 154 controls the rate at which gasses are exhausted from the processing region into the plenum chamber interior to be exhausted out through the chamber exhaust port 202. A throttle may be coupled between the exhaust port 202 and the pump 200 to further regulate the flow of material from the plenum chamber 326. An isolation
10 valve coupled to the exhaust port 202 can facilitate a unidirectional gas flow.

[0030] The outlet flow restrictor 154 includes a movable flow restrictor body 350 which, in the illustrated embodiment moves between an open position as shown in Fig. 1 and a closed position as depicted in Fig. 3.
15 The flow restrictor body 350 is also generally annular shaped and defines an annular shaped flow restrictor engagement surface 352 which engages an opposing annular-shaped flow restrictor seat surface 354 disposed on the lid portion 302 when the flow restrictor is in the closed position as shown in Fig. 3. The flow restrictor passageway 156 is defined by the annular space
20 between the flow restrictor engagement surface 352 and the flow restrictor seat surface 354, each of which completely surrounds the processing region 142 above the substrate support 102. Thus when the flow restrictor 154 is open, the flow restrictor passageway 156 provides a narrow, uniform gap for exhaustion of gases in which the gap is present around the whole periphery
25 of the substrate. Alternatively, the gap 156 of the flow restrictor can also be formed by a series of openings placed uniformly around the periphery of the substrate.

[0031] It is recognized that the flow restrictor opening or openings 156 can be shaped and positioned as desired to achieve the desired flow
30 patterns from the chamber. For example, the flow restrictor including the flow restrictor body and seat may be circular shaped as shown in Fig. 4,

rectangular shaped or have another shape, depending upon the shape of the chamber and the shape of the substrate being processed. In addition, the flow restrictor passageways 156 can be positioned to provide an exhaust flow which can offset an imbalance that might be caused by vacuum pumping from only one side of the substrate and plenum chamber. As a result, more uniform exhaust around the whole periphery of the substrate might be achieved, even at high gas pressures.

[0032] It is further recognized that the flow restrictor may have a single body formed of a single member such as the illustrated body 350.

Alternatively the flow restrictor can have a plurality of flow restrictor bodies disposed around the chamber as needed. In a preferred embodiment, the flow restrictor body or bodies and the flow restrictor passageway or passageways are disposed on at least two sides of the substrate to draw exhaust gasses more uniformly from the chamber as compared to an exhaust outlet disposed on just one side of the substrate.

[0033] The walls of the chamber body 304 may be shaped to form a continuous and smoothly tapering flow path for the exhaust gas to reach the passageway 156, which may further reduce the accumulation of particles in the chamber body 304 and the exhaust passageway 152. Because the plenum chamber 326 is generally large with respect to the flow restrictor passageway 156, and is open around its whole circumference via exhaust passageway 152, it is believed that good and uniform evacuation from the whole of the plasma/processing region 142 may be facilitated.

[0034] In the illustrated embodiment, the heater 128 is affixed to the substrate support 106 which in turn is affixed to the walls 104 of the chamber. Hence, the heater 128 and the substrate support 106 in the illustrated embodiment do not move. It is appreciated that in other applications, a movable heater and substrate support may be desirable. However, in those applications in which the heater and substrate support are fixed and do not move, the chamber interior may be made more compact. As a consequence, the chamber may be filled with processing gas and the residue gasses

evacuated from the chamber more quickly..

5 [0035] The exhaust flow restrictor body 350 may be actuated between open and closed positions using any suitable actuator, depending upon the particular application. For example, in the chamber 100 of the illustrated embodiment, the flow restrictor body 350 is actuated by a plurality of push rods 400 (Fig. 1) which extend below the level of the substrate support surface 106. The flow restrictor body 350 may slide against a chamber wall surface 430 (Fig. 3) to direct the movement of the flow restrictor body. In addition, the flow restrictor body 350 may engage more than one
10 flow restrictor seat surface as indicated by the secondary flow restrictor seat surface 440 in Fig. 3.

[0036] The movements of the push rods (and the associated flow restrictor body 350) may be controlled by one or more controllers represented schematically by a controller 450 in Fig. 1. Other components including the
15 gas inlet 140, substrate port 124 and heater 128 may be controlled by the controller 450 as well. The controller 450 may be implemented, for example, by a programmed workstation. It is contemplated that hardwired controllers may be used as well.

[0037] In the embodiment of Fig. 1, the substrate support 102 has
20 an outer periphery and the flow restrictor body 350 has an inner periphery. To reduce the chances of particulates falling on the substrate, it is preferred if the flow restrictor body inner periphery is positioned entirely outside the substrate support outer periphery as shown in Fig. 4.

[0038] In the embodiment illustrated in Fig. 1, the exhaust plenum
25 326 is formed between the underside of the lid 302 and upper walls of the chamber body portion 304. Alternatively, the exhaust plenum may be formed entirely in the body portion or entirely in the lid portion, depending upon the particular application. Figs. 5 and 6 show an alternative chamber embodiment 600 in which a lid portion 604 includes an exhaust plenum
30 chamber 606 and a central cover 608. The lid portion 604 is pivotally coupled to the chamber body portion 610 by a hinge 612. A pressure vessel is

formed when the lid portion 604 is closed onto the body portion 610 in a manner similar to that of the chamber 100 of Fig. 1.

[0039] The chamber 600 also includes a non-sealing flow restrictor 618 which has a movable body 620 which moves between an open position as depicted in Fig. 5 and a closed position as depicted in Fig. 6. The flow restrictor body 620 is generally disk-shaped and defines an annular shaped flow restrictor engagement surface 622 which engages an opposing annular-shaped flow restrictor seat surface 624 disposed on the plenum chamber when the flow restrictor is in the closed position as shown in Fig. 6. A flow restrictor passageway 626 is defined by the space between the flow restrictor engagement surface 622 and the flow restrictor seat surface 624, each of which completely surrounds the processing region 632 above the substrate support 102. Thus when the flow restrictor 618 is open, the flow restrictor passageway 626 provides a narrow, uniform gap for exhaustion of gases in which the gap is present around the whole periphery of the substrate. Alternatively, the gap 626 of the flow restrictor opening can also be formed by a series of openings placed uniformly or as desired around the periphery of the substrate. In the open position, the upper side 640 of the flow restrictor body 620 engages a second annular-shaped flow restrictor seat surface 642 disposed on the plenum chamber to inhibit the passage of exhaust gasses between the flow restrictor body 620 and the lid central cover 608.

[0040] In the embodiment, of Fig. 5, the flow restrictor body 620 is actuated by a central push rod 650 which is journaled for vertical movement in the lid central cover 608. Movement of the push rod 650 actuates the flow restrictor body 620 between the open and closed positions. In some applications it is not desirable for moving parts to be positioned above the substrate due to the increased risk of particles being generated over the substrate. However, in other applications the benefits of such a design may outweigh the increased risks.

[0041] In the illustrated embodiment, the substrate 108 is lowered to and lifted from the substrate support surface 106 by lift fingers 126. In this

embodiment, the movable bodies of the flow restrictors together with the lift fingers 126 are selectively actuated by push rods journaled for vertical movement in the chamber wall. Pressure-tight seals may be provided around the rods to maintain the vacuum pressure of the pressure vessel.

5 **[0042]** A process in accordance with the present inventions may be used to deposit a variety of deposition materials to form a variety of deposited materials. The deposition gas may include one or more different gasses which deposit material onto the substrate. The gasses may react chemically prior to deposition or may react with material previously deposited onto the
10 substrate. Other deposited materials may be deposited in a relatively pure form. Examples of suitable deposition materials are believed to include tantalum, tantalum nitride, tantalum oxide, titanium, titanium nitride, tungsten, tungsten silicide, silicon nitride, and aluminum oxide. Although the processes of the illustrated embodiment have been described primarily in connection
15 with deposition gasses, it is recognized that a chamber in accordance with the present inventions may be used with other processing gasses including gasses which react with the substrate but do not deposit a significant amount of material onto the substrate.

[0043] The chamber 100 may also have a plasma generator to
20 generate a plasma to activate the deposition gas or other processing gas. Heating the substrate with the heater 128 can in some processes, accelerate the deposition process and also cause the deposition material to deposit preferentially onto the substrate rather than other interior surfaces of the chamber. In addition, in some applications, a dispersal plate may be used to
25 distribute the deposition gas. Dispersal plates are often used to promote uniformity, particularly in low quantity, fast depositions. Alternatively, a dispersal plate may be omitted, particularly in relatively long deposition processes in which the substrate is permitted to soak in a large quantity of the deposition gas.

30 **[0044]** It will, of course, be understood that modifications of the illustrated embodiments, in their various aspects, will be apparent to those

skilled in the art, some being apparent only after study, others being matters of routine mechanical and electronic design. Other embodiments are also possible, their specific designs depending upon the particular application. As such, the scope of the invention should not be limited by the particular
5 embodiments described herein but should be defined by the appended claims and equivalents thereof.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
222